

## Uninsulated Flexible Ducting 10m



### CONSTRUCTION

ALUMINIUM UNINSULATED FLEX IS A REINFORCED ALUMINIUM AND POLYESTER LAMINATED DUCTING WITH AN ENCAPSULATED HIGH TENSILE STEEL WIRE HELIX.

### ADVANTAGES

- \* SUPPLIED IN STANDARD 10 METER LENGTH, COMPRESSED TO 0.6 MTS.
- \* CAN BE CUT TO INDIVIDUAL LENGTH.
- \* EASY TO CONNECT TO EITHER ROUND OR OVAL DUCTING.
- \* NO SPECIAL TOOLS REQUIRED FOR CUTTING OR FIXING.
- \* IN THE EVENT OF FIRE NO TOXIC GASES ARE EMITTED.
- \* THE PRODUCTS HAVE BEEN SUCCESSFULLY TESTED AND FIRE RESISTANCE RATED

### TECHNICAL DATA

CONSTRUCTION MATERIAL.....REINFORCED ALUMINIUM/POLYESTER  
 NON-CORROSIVE TO STEEL, COPPER, ALUMINIUM AND ZINC.  
 WIRE PITCH.....24MM  
 DIAMETER RANGE.....80-610MM  
 TEMPERATURE RANGE.....-30/+130°C  
 MAXIMUM AIR VELOCITY.....30 M/SEC  
 POSITIVE WORKING PRESSURE.....2300 PA (MAX)  
 STANDARD LENGTH.....10 METERS  
 PACKING.....INDIVIDUAL BOX OF 0.6 METERS  
 CLAMPING.....LIGHTENING BAND, STAINLESS STEEL FLEX CLIPS.